

ELKA

designer floors for living

14mm ENGINEERED Loc FLOORING



Available: Brushed & Oiled / Lacquered.

Appearance General

Colour:

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain:

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

Variations Within Species And Grades:

- Considerable variation among boards in colour and grain texture.

Specification:

- Grade: Rustic 'B\C\D'
- Bevel: G2 0.5mm 'long edge only'
- Oak origin: Russia/China
- 14mm x 150 x 1390mm, 3mm wear layer
- Pack Size: 1.668 M2
- Lacquer : 6 coats
- Oil: 2 coats
- Lacquer: Treffert
- Oil brand: Woca
- Core species: Poplar Block
- Adhesive: Akzo Nobel
- FSC/PEFC certificate: No
- Janka score: 1360 'medium hardness'
- Warranty: 25 Years

See www.elkaflooring.com for warranty information

Workability

Installation:

- DIY & Professional

Sanding:

- Good if the correct sanding sequence is followed

Installing methods allowed:

- Floating over underlay

Features and Advantages:

- Quick and easy to install
- Stronger than glue
- No glue required
- Can be uplifted / refitted
- Can be laid over under floor heating
- Can be sanded and re-finished
- Made 100% of natural wood
- Ensures excellent thermal and acoustic insulation
- Dimensional stability
- Floor can be laid in all residential areas (except those of high humidity)
- Elka complimentary accessory products available – underlay, finishing profiles & maintenance products. View these at www.elkaflooring.com



engineered flooring

- 1 finish
- 2 Hardwood wear layer
- 3 Engineered real wood core
- 4 Stabilising backing board.

